



ATLANTIC MAX POWER 5000 ENGINE OIL SAE 20W-50 API SL

(Premium Quality Multigrade Oil)

DESCRIPTION

ATLANTIC MAX POWER ENGINE OIL SAE 20W-50 API SL is premium quality engine oil developed to the highest standards of lubricant quality, reliability and dependable protection.

APPLICATIONS

ATLANTIC MAX POWER ENGINE OIL SAE 20W-50 API SL is suitable for a variety of automobiles, modern, high-output, multivalve, turbocharged & supercharged Gasoline powered passenger cars and Diesel powered light duty vehicles. These superior grade, highly shear-stable, multi-grade gasoline engine oils are formulated for passenger cars and light truck engines requiring optimum performance under all operating conditions.

PROPERTIES

ATLANTIC MAX POWER ENGINE OIL SAE 20W-50 API SL is specially formulated with high viscosity index mineral oil utilizing latest additive technology, shear stable polymer and efficient detergent additive package to provide reliable engine protection under extremely severe operating condition. This oil is also approved by leading car manufactures and meets the latest industry standards for service fill use.

PERFORMANCE FEATURES AND BENEFITS

- Excellent oxidation stability to reduce engine deposits and sludge build-up to keep engines running reliably
- Enhanced low temperature capabilities for flawless cold weather starting
- Excellent engine cleanliness and lower combustion residues.
- Excellent high and low temperature properties to provide dependable protection across a wide range of driving conditions
- Good protection against rust and corrosion
- Superior dispersants provide excellent control over soot induced oil thickening.

RECOMMENDATIONS / SPECIFICATIONS

International Standards : API SL, SL/CF, ACEA: A3/B3

Meets quality requirements of most gasoline engine manufacturers in the USA, Europe, Japan and Korea

TYPICAL TECHNICAL PROPERTIES

Viscosity Grade, SAE J300	20W-50
PRODUCTS CODE:	PCMO-24116
Density at 15°C, g/ml, ASTM D4052	0.892
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	8500 @-15°C
Kinematic Viscosity at 40°C, mm²/s, ASTM D445	176.4
Kinematic Viscosity at 100°C, mm²/s, ASTM D445	19.2
Viscosity Index, ASTM D2270	124
Flash Point(COC), °C, ASTM D92	238
Pour Point, °C, ASTM D97	-24
Total Base Number (TBN), mg KOH/g, ASTM D2896	7.2

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.

ATL/PDS/AL/06-12405AL/02*, 04.07.24, Page 1/1

* supersedes all previous versions

Packing : 700 ml ,800 ml , 1L , 2L, 3L, 4L, 5L, 6.5L, 7L, 8L,16L,18L, 20L, 25L, 200L, 205L, 208L, 210L

