



ATLANTIC ANTIFREEZE COOLANT CONCENTRATE-BLUE

EXTENDED LIFE COOLANT/ANTIFREEZE

DESCRIPTION

ATLANTIC ANTIFREEZE COOLANT CONCENTRATE-BLUE for EUROPEAN VEHICLES is a line of premium coolants specifically designed to match the technology and color requirements of European vehicles. Each coolant is formulated with the same corrosion inhibitor technology that protected your vehicle straight from the factory. These formulas will provide excellent protection against rust and corrosion to all cooling system metals, including aluminum, and are fully compatible with other extended life coolants. Color cues on the packaging and a list of covered vehicles on the front label make it easy to identify the right match for your specific vehicle.

APPLICATIONS

ATLANTIC ANTIFREEZE COOLANT CONCENTRATE-BLUE is specifically engineered for use in all European vehicles requiring a BLUE SILICATE-ENHANCED HOAT extended life antifreeze + coolant.

PROPERTIES

ATLANTIC ANTIFREEZE COOLANT CONCENTRATE- BLUE is an ethylene glycol-based antifreeze/coolant specifically developed for use in any European vehicle requiring a silicate-enhanced Blue formula. It contains high-quality hybrid organic acid (HOAT) corrosion inhibitors and is free of nitrite, phosphate and amines chemicals. IT meets the performance requirements of ASTM D3306 and BS 6580. With a complete flush and fill, ATLANTIC ANTIFREEZE COOLANT CONCENTRATE- BLUE guarantees it will provide service life protection of up to 150,000 miles or 5 years.

PERFORMANCE FEATURES AND BENEFITS

- Matches each European vehicle manufacturer's technology and color requirements
- Protects all cooling system metals from rust and corrosion
- Meets the performance requirements of ASTM D3306 and BS 6580
- Service life of up to 5 years/150,000 miles with a complete cooling system flush and fill
- Color-coding and vehicle applications listed on the front simplify selecting the right antifreeze/coolant
- Available as both concentrate and 50/50 prediluted products to do the job right

	SERVICE TO BE PERFORMED	
RECOMMENDED PRODUCT	TOP-OFF	FLUSH/FILL
CONCENTRATE	Yes	Yes
50/50 PREDILUTED	Yes	

RECOMMENDATIONS / SPECIFICATIONS

• Audi: Pre-1996 • BMW: All • Dodge: All Sprinter • Jaguar: Pre-1997 • Mercedes-Benz: Pre-2014 • Mini: All
• Porsche: All 924, 928, 944, 968 • Range Rover V8 and Diesel: 1990-2005 • Saab: Pre-2000 • VW: Pre-1996 • Volvo: All

TYPICAL TECHNICAL PROPERTIES

PRODUCT CODE:	ASP-COOL-25006		
CHARACTERISTIC	CONCENTRATE	50/50	ASTM D3306 LIMITS
Appearance, visual	Blue	Blue	-
Specific gravity, ASTM D1122	1.120-1.130	1.070-1.080	7.0-11.0
pH, (50% vol), ASTM D1287	10.5	10.5	1.110-1.145
Boiling point, °C (°F), ASTM D1120	163(325)	109 (229)	108 (226) Min
Freezing point, °C (°F), ASTM D1177	---	-37.9 (-36.2)	-36.4 (-33.5) Max
Effect on Automotive Finish, ASTM D1882	No Effect	No Effect	No Effect
Total water, mass %, ASTM D1123	<5	50	5 Max*
Ash content, mass %, ASTM D1119	<5	<2.5	5 Max*
Chloride, ppm, ASTM 3634	<25	<25	25 Max

*concentrate only

Packing: 1L, 4L, 5L, 20L, 200L, Bulk

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.

ATL/PDS/ASP-11/02*, 01.06.25, Page 1/1

* supersedes all previous versions